


Tymbia

Handling & Warehouse Equipment

CDD12J/CDD12JD Electric pallet stacker

Characteristics:



1. High-power and high-performance lifting pump has high efficiency.
2. Side driving design gives the truck a small steering radius and broadened view.
3. The driving system with permanent magnetic motor has small volume, light mass, small loss.
4. Water-proof inching switch imported from German meets the requirements of harsh working condition such as cold, humidity and dust circumstances.
5. Four colors LED electricity meter makes it simple and direct to read.
6. External positioned charger has better cooling performance.
7. It's more comfortable and easy for operation using a super long handle that integrates lifting button, key switch, electricity meter, which is suitable for ergonomics; more accurate speed control with the turtle speed switch; more durable with the high quality air-pressure springs which allows slowly and automatically reset.
8. Iron steel guard with high density is durable, firm and has high protection effect.



CDD12J/CDD12JD Electric pallet stacker

Manufacturer's Data and Design Characteristics

Characteristics		Tymbia						
1.01	Manufacturer	Tymbia						
1.02	Model	CDD12J				CDD12JD		
1.03	Operation	Pedestrian propelled						
1.04	Rated traction weight	Q (kg)	1200					
1.05	Mast type	Single mast	2-Stage STD				Single column	
1.06	Lift	h3 (mm)	1600	2000	2500	3000	3500	1600
1.07	Capacity at highest height	kg	1200	1050	900	750	600	1200
1.08	Service weight with battery	kg	425	441	453	465	477	395
1.09	Load centre	c (mm)	600					
1.10	Axle centre to fork face	x (mm)	710					
1.11	Wheel base	y (mm)	1154				1031	
1.12	Controller	CURTIS						
Wheels/Tyres								
2.01	Wheels type	Polyurethane						
2.02	Driving wheel size	φ × w (mm)	φ210 × 70					
2.03	Bearing wheel size	φ × w (mm)	φ80 × 70					
2.04	Additional wheels (dimensions)	φ × w (mm)	φ150 × 58					
2.05	Wheels, number front/rear (x = driven)	1x+1/4						
Dimensions								
3.01	Height of mast, lowered	h1 (mm)	2014	1494	1744	1994	2244	1990
3.02	Height of mast, extended	h4 (mm)	2014	2424	2924	3424	3924	2060
3.03	Fork Height, Lowered	h13 (mm)	86					
3.04	Overall length	l1 (mm)	1755				1632	
3.05	Length to fork face	l2 (mm)	605				482	
3.06	Overall width	b1/ b2 (mm)	795					
3.07	Fork dimensions	s/a1 (mm)	60/160/1150					
3.08	Width of forks	b5 (mm)	570/650/695					
3.09	Min. Ground clearance	m2 (mm)	24					
3.10	Aisle width with pallet 1000 × 1200 across forks	Ast (mm)	2068				2048	
3.11	Aisle width with pallet 800 × 1200 along forks	Ast (mm)	2034				2014	
3.12	Min. Turning radius	Wa (mm)	1366				1316	
Performance								
4.01	Travel speed, with/without load	(km/h)	4.0/4.2					
4.02	Lifting speed, with/without load	(mm/s)	92/136					
4.03	Lowering speed, with/without load	(mm/s)	112/98					
4.04	Max. gradeability laden/unladen	(%)	6/8					
4.05	Service brake	Electromagnetic brake						
Drive								
5.01	Drive motor, output S2 60 min.	(kW)	0.75					
5.02	Lift motor rating at S3 15%	(kW)	2.2					
5.03	Battery according to DIN 43531/35/36 A,B,C,no		no					
5.04	Battery voltage/rated capacity	(V/Ah)	2 × 12/100					
5.05	Battery weight (± 5%)	(kg)	2 × 27					
Others								
6.01	Noise level at operator's ear	(dB(A))	69					
6.02	Steering type	Mechanical steering						



www.tymbia.com | info@tymbia.com